

# NASA TECH BRIEF



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Division, NASA, Code UT, Washington, D.C. 20546.

## Heat-Rejection Windows for Telescopes

Heat-rejection windows have been constructed for telescopes to reflect incident solar energy outside the hydrogen-alpha line while processing a peak transmission exceeding 50% at 6563 Å. The original requirement was telescope windows for monitoring of the solar disk at the hydrogen-alpha line; they were to reduce the solar heat load at the entrance apertures of the telescopes.

The newly designed window comprises two elements mounted in a cell of aluminum alloy. The outer element is primarily an ultraviolet reflector transmitting visible and near-infrared incident solar energy. The inner element bears a multilayer dielectric coating that transmits 80% of incident sunlight in a 300-Å passband centered near 6563 Å. Energy beyond the main spectral band is almost wholly reflected (reflectance is 0.99 between 4100 Å and the far infrared). A window's secondary function is as a secondary blocking filter to a telescope's Fabry-Perot filter.

Fused silica is the substrate of both elements; it was chosen for its transmission properties and its resistance to browning by radiation. The outer ele-

ment is made necessary by the fact that the high-index dielectric material on the inner one shows considerable absorption at wavelengths shorter than 4000 Å. Coatings have been uniformly deposited over 8-in.-diam clear apertures with equipment for automatic control of rate and thickness.

### Note:

Requests for further information may be directed to:

Technology Utilization Officer  
Marshall Space Flight Center  
Huntsville, Alabama 35812  
Reference: B70-10386

### Patent status:

Inquiries about obtaining the rights for commercial use of this invention may be made to NASA, Code GP, Washington, D.C. 20546.

Source: R. Austin and J. Rehnberg of  
Perkin-Elmer Corp.  
under contract to  
Marshall Space Flight Center  
(MFS-20634)

Category 04